

S9 (Front Recording Button)

Android body camera

A SPIKECAM Android 12 camera with a front recording button, 2.8-inch touchscreen, removable battery and external USB camera input.



Product view

Button and touch control

Start recording from the front button. Dedicated PTT, SOS, photo and audio buttons complement the touchscreen.

External camera input

USB OTG supports an external 1080p camera, alongside built-in front and rear cameras and dual-stream support.

Record around an event

Choose pre-recording up to 120 seconds and post-recording up to 300 seconds. A tag button supports event handling.

Android 12

Device operating system

2.8-inch touch

Capacitive display

1440p

Base video mode

PLAN YOUR PRODUCT CONFIGURATION

Talk to Peter Pen about your application, model and project.

[Email Peter](#)

[Call +86 13798434740](#)

SPIKECAM LIMITED

Hong Kong: 10/F, Corporation Park, 11 On Lai Street, Sha Tin, New Territories, Hong Kong

Peter Pen

info@spikecam.com

[Tel / WhatsApp: +86 13798434740](#)

spikecam.com

Technical specifications

System and storage

Operating system	Android 12
Processor	8-core; 64-bit
RAM	2 GB
Internal storage options	16 GB; optional 64 / 128 GB
TF-card storage	32 GB listed; expandable to 256 GB
Display	2.8-inch capacitive multi-touch; 480 x 640 pixels
Language	English

Cameras, video and audio

Built-in cameras	Front: 2 MP; rear: 4 MP
Video modes	2560 x 1440 / 1920 x 1080 / 1280 x 720 / 720 x 480
Video format	MP4; H.264; dual-stream support
Photo output	Up to 54 MP; JPEG
Digital zoom	Up to 24x
External video input	1080p USB camera via OTG; confirm camera model
Audio	Two built-in microphones; AAC; 2 W speaker
Lighting	Four IR lights; one white light; aiming laser
White balance	Automatic

Recording and controls

Pre-recording	5 / 10 / 20 / 30 / 60 / 120 seconds
Post-recording	5 / 10 / 20 / 30 / 60 / 120 / 300 seconds
Recording control	Front button; one-touch recording
Shortcut buttons	Power, video, audio, photo, SOS, PTT, tag and FN
Recording functions	Playback; motion detection; OSD watermark
Feedback	Vibration motor; text-to-speech voice broadcast
Sensors	Built-in G/M sensor

Technical specifications

Wireless and platform

LTE-FDD bands	B1 / B2 / B3 / B4 / B5 / B7 / B8 / B20 / B28A/B
LTE-TDD bands	B38 / B39 / B40 / B41
Other cellular bands	GSM B2 / B3 / B5 / B8; WCDMA B1 / B5 / B8
Wi-Fi	2.4 GHz and 5 GHz; 802.11 a/b/g/n/ac
Bluetooth	5.0
Positioning	GPS / BDS / GLONASS / Galileo
Optional NFC	External antenna required
Platform and interfaces	CMSV; ONVIF; RTMP
Voice intercom	Group and end-to-end intercom
Optional recognition	Facial and license-plate recognition

Interfaces, power and physical data

SIM slot	One Nano-SIM
USB ports	One USB-C; one Micro USB 2.0
USB functions	Charging; OTG; software updates; data copy
Battery type	Removable
Dimensions	93 x 70 x 26 mm
Weight	166 g without clip
Operating temperature	-20 to +55 C
Storage temperature	-20 to +60 C
Operating humidity	40-80 percent RH
Recording duration	10 hours at 720p

Configuration notes

Specify S9 (Front Recording Button) when selecting firmware, batteries and accessories.

Confirm carrier bands, CMSV licensing, ONVIF/RTMP integration and the external USB camera model.

NFC needs an external antenna; recognition features are optional. Confirm storage and package contents.

Recording duration is 10 hours at 720p. Battery capacity and radio, screen and infrared test settings remain unconfirmed.